

04-10-00

A

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

UTILITY PATENT APPLICATION TRANSMITTAL LETTER

Atty./Agent Docket No.: CAS0027Mailing Date: April 7, 2000Express Mail Label No.: EJ923752189US

JC675 U.S. PTO

09/545446

04/07/00

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

Dear Sir:

Transmitted herewith for filing under 37 CFR 1.53 (b) is a Non-provisional Utility Patent:

X New Application; or a Continuation, Division, or Continuation-in-Part (CIP) Application of prior US application No. , filed on , having US Examiner , in Group Art Unit : of

Inventor(s): Nandakishore A. Albal
Walter Blackwell Cook, Jr.

For (Title): SYSTEM AND METHOD FOR LOCATING AN END USER

This transmittal letter has 2 total pages.

Enclosed are:

X 4 sheets of drawings, along with 29 pages of specification, claims, and abstract.X Oath or Declaration Combined with Power of Attorney (4 pages)X Newly Executed (original) Copy from a prior application (if this is a Continuation/Division with no new matter) Statement deleting named inventor(s) in prior application if this is a Continuation/Division (See 37 CFR 1.63(d)(2) and 1.33(b).) Consider as the above Statement, Please delete as inventors for this application the following inventors named in the prior application: .

 A certified copy of a (non-US) application S/N / , having a filing date of , and foreign priority to this non-US application for the present application is hereby claimed under 35 USC 119.

X An Assignment Transmittal Letter and Assignment of the invention to MOTOROLA, INC. An Information Disclosure Statement (IDS), with PTO-1449, and citation copies. Preliminary Amendment Petition For Extension of Time for parent application of the present Continuation/Division/CIP applicationX PrintEFS DocumentX Return Receipt Postcard

Instructions:

 Incorporation by Reference (for Continuation/Division application) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

 Since the present application is based on a prior US application, please amend the specification by adding the following sentence before the first sentence of the specification: "The present application is based on prior US application No. / , filed on , which is hereby incorporated by reference, and priority thereto for common subject matter is hereby claimed."

 Please cancel filed claims .

 X The filing fee is calculated as follows:

CLAIMS AS FILED, LESS ANY CANCELED BY AMENDMENT

	NUMBER OF CLAIMS	NUMBER EXTRA	RATE	FEE
TOTAL CLAIMS	21- 20 =	1	X \$18	= \$18.00
INDEPENDENT CLAIMS	7- 3 =	4	X \$78	= \$312.00
MULTIPLE DEPENDENT CLAIMS			\$260	= \$ 0.00
			BASIC FEE	= \$ 690.00
			TOTAL FILING FEE	= \$1,020.00

 X Please charge Deposit Account No. 13-4772 in the amount of \$ 1,020.00 for the Total Filing Fee. Two duplicate copies of this sheet are enclosed.

 X The Commissioner is hereby authorized to charge any additional fees which may be required now or in the future under 37 CFR 1.16 or 37 CFR 1.17, including any present or future time extension fees which may be required, or credit any overpayment to Deposit Account No. 13-4772. Two duplicate copies of this sheet are enclosed.

Please forward all correspondence to:

Customer Number **22917**

By: 

James E. Gauger
Registration No. 38,154
MOTOROLA, INC.
Phone: (847) 576-0053
Fax: (847) 576-3750

[illegible]

CORRESPONDENCE INFORMATION

APPLICATION INFORMATION

Source:: PrintEFS Version 1.0.1

SYSTEM AND METHOD FOR LOCATING AN END USER

5 FIELD OF THE INVENTION

The present invention relates to communication systems, and, more particularly, to a method and system for locating an end user.

10 BACKGROUND OF THE INVENTION

Typically, global location systems can determine the location of an object, such as a ship or an aircraft, anywhere on the earth. One example of a presently-known location system is the Global Positioning System (GPS).

15 GPS can determine the location of an object, in terms of latitudinal and longitudinal coordinates.

However, conventional GPSs, and other global location systems, are currently not included within end user communication devices, including, for example, cellular telephones and pagers. Such communication devices
20 would allow these location systems to serve the additional functions of locating end users and/or for allowing end users to be found.

Accordingly, it would be desirable to have a system and method, which allows for the location of end users, as well as for the authorization of end users to be found, that overcomes the disadvantages described above.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an embodiment of a communication system in accordance with the present invention;

- 5 **FIG. 2** is a block diagram of another embodiment of a communication system in accordance with the present invention;

FIG. 3 is a flowchart of an embodiment of an end user location routine;

FIG. 4 is a flowchart of another embodiment of an end user location routine; and

- 10 **FIG. 5** is an exemplary block diagram of another embodiment of a communication system, in accordance with the present invention.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

FIG. 1 is a block diagram that illustrates an embodiment of a
5 communication system **10**. The communication system **10** generally includes
one or more network access devices or communication devices **12, 22**,
communication networks **14, 18, 34**, one or more assistance centers **38** (one
being shown), and a communication node **16**. As further described below,
the communication system **10** can provide various services and capabilities to
10 cellular end users, wire-line telephone end users, paging end users, satellite
end users, mobile or portable telephone end users, trunked end users,
computer network end users (e.g., Internet or Intranet end users), wireless
data end users, branch office end users and the like.

The communication devices **12, 22** of the communication system **10**
15 can be utilized by end users **20, 32** to access and/or connect with the
communication node **16**. The communication devices **12, 22** can include, but
are not limited to, wireline telephones, mobile telephones, paging units, radio
units, wireless data devices, Web telephones, portable or wireless
telephones, personal information managers (PIMs), personal digital assistants
20 (PDAs), personal computers (PCs), network televisions (TVs), Internet TVs,
Internet telephones, portable wireless devices (i.e., two-way pagers), security
systems (both mobile and premises-based), workstations or any other
suitable communication devices.

Regardless of its specific form, the communication devices **12, 22** have
25 user-input interfaces **24, 26** and/or user-output interfaces **28, 30**. The user-
input interfaces **24, 26** are for receiving input from the end users **20, 32** and
the user-output interfaces **28, 30** are for providing output to the end users **20**,
32. The user-input interfaces **24, 26** can include, but are not limited to, an
electroacoustic transducer, such as, for example, a microphone to receive
30 voice and other audible input from the end users **20, 32**, a keypad or a
keyboard to receive key strokes from the end users **20, 32**, a touchpad or
touchscreen to receive touch input from the end users **20, 32**, and a pointing

device such as a mouse or a trackball to receive point and click inputs from the end users **20, 32**. The user-input interfaces **24, 26** may further include an assistance request button or key. When the assistance request button is depressed or activated, the communication devices **12, 22** can transmit an assistance request signal to the communication node **16**, as further described below.

The user-output interfaces **28, 30** of the communication devices **12, 22** can include, but are not limited to, an electroacoustic transducer such as, for example, a speaker to provide voice and other audible output to the end users **20, 32**, and a visual display device such as a liquid crystal display or a cathode ray tube to provide graphical and/or textual information to the end users **20, 32**. It is noted that each of the communication devices **12, 22** may include more than one user-input interface **24, 26** and more than one user-output interface **28, 30**. For example, a wireless telephone may have a microphone, a telephone keypad, a speaker, and a visual display device.

The communication devices **12, 22** may also include a Global Positioning System (GPS) chip, or other similar locator system which would allow the communication devices **12, 22** to determine their geographic location. It will also be recognized that the geographic location of the communication devices **12, 22** may be determined by an communication infrastructure-based system (i.e., cell and sector coordinates). Once the communication devices **12, 22** determine their geographic location, the communication devices **12, 22** may transmit their geographic location to the communication node **16**. The communication devices **12, 22** may also transmit pre-recorded messages to the communication node **16**. These pre-recorded messages may include, for example, a "Help Needed" message that specifies the situation in which assistance may be needed. The communication devices **12, 22** may also have the ability to accept messages from the communication node **16** and to provide the response to the end users **20, 32**. The communication devices **12, 22** may be able to transmit the message to the end users **20, 32** even if the communication devices **12, 22**

have been turned off by using, for example, an internal battery or other suitable apparatus.

The communication devices **12, 22** communicate with the communication node **16** via the communication networks **14, 18**. The communication networks **14, 18** can interface with the communication devices **12, 22** through wireline or wireless networks or systems (i.e., telephone or televisions systems, Integrated Services Digital Network (ISDN) systems, coaxial lines, computer networks, digital end user lines, private networks, wireless local loop systems, etc.). It should be noted that the communication network **34** can interface with the assistance center **38** through similar systems and networks.

The communication networks **14, 18, 34** of the communication system **10** can include, but are not limited to, intranets, extranets, the Internet, a Local Area Network (LAN), a telephone network, (e.g., a Public Switched Telephone Network (PSTN), private telephone networks, etc.), a cellular network, satellite networks, a personal communication system, a TV network (e.g., a cable TV system), local, regional, national or global paging networks, an email system, a wireless data network (e.g., satellite data or local wireless data networks), a wireless LAN, a wireless local loop/distribution system (e.g., LMDS, MMDS or Code Division Multiple Access (CDMA) based system), a Voice Over Internet Protocol (VOIP) network, or any other suitable network. The communication networks **14, 18, 34** can also include a wide area network (WAN), such as, for example, the Internet, the World Wide Web (WWW) or any other similar on-line service. It will be recognized that the communication networks **14, 18, 34** may have portions in common, may comprise two separate networks, or may be the same network.

The communication node **16** of the communication system **10** can include, but is not limited to, an interactive voice response node, a server computer, the MIX™ platform and the Myosphere™ service provided by Motorola, Inc. of Schaumburg, IL (as further described with reference to **FIG. 5**), or other suitable system. It will be recognized that the communication

node **16** may be integrated within or may be remote from the communication networks **14, 18, 34**.

The communication node **16** can preferably send queries or messages to the communication devices **12, 22**, accept responses from the communication devices **12, 22**, and provide the geographic location of the communication devices **12, 22** to other end users **20, 32**. The communication node **16** may store such designations, along with any other preferences, within an end user profile, which may be preferably located within a memory device located integral with, or remote from, the communication node **16**.

The assistance center **38** of the communication system **10** may be a type of public assistance center, such as, for example, a 9-1-1 center, which dispatches emergency and rescue assistance to the general public. The assistance center **38** is preferably operatively connected to the communication node **16** via the communication network **34**. It should be recognized that the assistance center **38** can be directly linked to the communication node **16** by, for example, a telecommunication link. The assistance center **38** may also be integrated into the communication system **10** as shown in **FIG. 2**.

The assistance center **38** preferably provides assistance to end users **20, 32**. Customer service agents or electronic agents trained to respond to requests may staff the assistance center **38** by the end users **20, 32** for assistance. Assistance may take various forms, including, for example, providing emergency rescue assistance when the end user is in need of assistance or is in danger. Preferably, the assistance center **38** would be available at all times to assist the end users **20, 32**.

FIG. 3 illustrates one embodiment of a routine by which a communication node provides assistance to an end user. In general, a communication node receives an assistance request signal from a communication device, operated by an end user. The communication node then determines an assistance center in close proximity to the communication device. The communication node may determine the closest assistance

center to the communication device. If the assistance center does not respond or is unable to provide assistance, the communication node can contact another assistance center.

5 The communication node forwards the assistance request signal to the assistance center. The assistance center then dispatches the necessary assistance to the end user. Finally, the communication node forwards a response signal to the communication device, to inform the end user that assistance will be provided.

10 At block **500**, the communication node receives an assistance request signal transmitted from a communication device. The assistance request signal preferably includes geographical coordinates (i.e., longitudinal and latitudinal coordinates) corresponding to the location of the communication device. These geographic coordinates can be determined by utilizing a GPS chip incorporated in the communication device. The assistance request
15 signal may also include information relating to the identity of the end user, the battery status of the communication device, any potential need for emergency assistance, as well as any other information relevant to the end user or the situation. The assistance request signal may take the form of a page transmission, a SMS message, an email message or a voice transmission.
20 Alternatively, an assistance center may receive the assistance request signal directly from the communication device. After sending the assistance request signal, the communication device may change from an active mode to a passive mode to conserve battery power and to only respond to signals received from the communication node.

25 At block **510**, the communication node determines an assistance center in close proximity to the communication device. Preferably, the assistance center may be a type of public assistance center, such as, for example, a 9-1-1 center, which dispatches emergency and rescue assistance to the general public. In determining the appropriate assistance center, the
30 communication node preferably compares the location of the communication device, received in the assistance request signal, with the known locations of

surrounding assistance centers. The location of assistance centers throughout the world may preferably be stored in a database to which the communication node has access.

- Once the communication node has determined an assistance center to
- 5 provide assistance to the end user, the communication node will forward the assistance request signal to the assistance center at block **520**. Additional information relating to the end user, stored at or in communication with the communication node, may be sent along with the assistance request signal. This additional information may include, for example, pre-existing medical
- 10 conditions of the end user and other unique aspects of the end user. If not received along with the assistance request signal, the communication node can interact with the customer service agents or electronic agents at the assistance center at block **530** to provide any other information relevant to the end user, including, for example, the identity of the end user, the location of
- 15 the end user as well as any other information pertaining to the assistance and/or rescue of the end user, including, for example, any pre-existing medical conditions of the end user. Some or all of the requested information may reside at the communication node or in an end user database, which may be remote from or in communication with the communication node.
- 20 After a customer service agent or electronic agent decides to provide assistance to the end user, a response signal may be sent from the assistance center device to the communication node to inform the communication node that assistance will be provided to the end user. This response signal or any other suitable response message may then be
- 25 forwarded on to the communication device at block **540**. Preferably, the response signal may include a message informing the end user that assistance has been dispatched to their location. Additionally, the response signal may include instructions to the end user, such as, for example, "Stay Put", "Seek Shelter", etc.
- 30 In another embodiment, the communication node also possesses the ability to locate an end user upon receiving a request by a party wishing to

locate the end user as shown in **FIG. 4**. The communication node can allow the end user to designate under what specific conditions they wish to provide their geographic location to other end users or parties. At block **600**, the communication node receives an instruction signal sent by the party via a first communication device. The instruction signal is preferably a request from the party instructing the communication node to locate a particular end user. The communication node may require the party to provide identification to prove the party's authorization, such as, for example, by sending a password to the communication node.

10 After the communication node receives the instruction signal from the first communication device at block **600**, a second communication device of the end user will receive an information signal from the communication node at block **610**. The information signal alerts the end user that a query requesting the location of the end user has been transmitted to the communication node and/or to the communication device.

15 Once the second communication device receives the information signal, the end user may respond by transmitting a first response signal to the communication node at block **630**. In the first response signal, the end user will preferably indicate whether the end user wishes to provide the location of the end user. The first response signal may take the form of a page, an email message or a voice transmission. Furthermore, the first response signal may be inputted into the second communication device using either a voice-user interface (VUI), a graphical user interface (GUI), a keypad, or other suitable input apparatus.

20 In addition, the first response signal may include the location of the end user, as well as a unique identifying signal, used to identify the end user. This signal may include, but is not limited to, a personal identification number (PIN), a voice-, hand-, eye- or finger- print, etc., to assure the identity of the end user.

30 If the returned unique identifying method is incorrect or incomplete, the communication node may then be programmed to interpret such a response

as an indication that the end user is under duress and/or needs assistance. In such an event, the communication node may preferably proceed with a method for providing assistance to the end user, as the method described above with reference to **FIG. 3**.

5 Based on the first response signal, the communication node will transmit a second response signal to the first communication device at block **640**. As described above, the communication node transmits the second response signal if authorized to do so by the end user of the second communication device. Preferably, the second response signal will include
10 the location of the end user, as well as any other information the end user has authorized the communication node to transmit to the party. Furthermore, similar to the first response signal, the second response signal may take the form of a page, an email message or a voice transmission to the pre-authorized party via the communication node.

15 Referring now to **FIG. 5**, an exemplary block diagram of another embodiment of a communication system **200** having the capability to create and maintain an email usage record is illustrated. The communication system can implement the routines described in **FIGS. 3-4**, above.

 The communication system **200** generally includes one or more
20 communication devices **201, 202, 203, 204, 205** (five being shown), an electronic network **206**, and one or more information sources (e.g., content providers **208, 221** (two being shown) and data and voice markup language servers **209, 251, 253, 257**).

 The end user can access the electronic network **206** by dialing a single
25 direct access telephone number (e.g., a foreign exchange telephone number, a local telephone number, or a toll-free telephone number or PBX) from the communication device **201**. The end user can also access the electronic network **206** from the communication device **202** via the Internet **220** or WWW, from the communication device **203** via a paging network **211**, or from
30 the communication device **205** via a LAN, a WAN, an email connection or in any other similar manner.

As shown in **FIG. 5**, the electronic network **206** includes a telecommunication network **210** and a communication node **212**. The telecommunication network **210** is preferably connected to the communication node **212** via a high-speed data link, such as, for example, a T1 telephone line, a LAN, a WAN or a VOIP network. The telecommunication network **210** preferably includes a PSTN **214** and a carrier network **216**. The telecommunication network **210** can also include, for example, international or local exchange networks, cable TV networks, inter-exchange carrier or long distance carrier networks, cellular networks (e.g., mobile switching centers), PBXs, satellite systems, wireless data networks and other switching centers such as conventional or trunked radio systems (not shown), etc. The electronic network **206** can also include additional telecommunication networks, such as, for example, a wireless data network **207**.

The PSTN **214** can include various types of communication equipment, such as, for example, ATM networks, Fiber Distributed Data networks (FDDI), T1 lines, cable TV networks, VOIP networks and the like. The carrier network **216** generally includes a telephone switching system or central office **218**.

It will be recognized that the carrier network **216** can be any suitable system that can route calls to the communication node **212**, and the central office **218** can be any suitable wire-line or wireless switching system.

The communication node **212** is preferably configured to receive and process incoming calls from the carrier network **216** and the Internet **220**. The communication node **212** can receive and process pages from the paging network **211** and can also receive and process messages (e.g., emails) from the LAN, WAN, wireless data or email system **213**.

When an end user dials into the electronic network **206** from the communication device **201**, the carrier network **216** routes the incoming call from the PSTN **214** to the communication node **212** over one or more telephone lines or trunks. The incoming calls preferably enter the carrier network **216** through one or more "888" or "800" Inward Wide Area Telecommunications Services trunk lines, local exchange or long distance

trunk lines. It is also contemplated that the incoming calls can be received from a cable, cellular or VOIP network or any other suitable system.

The communication node **212** answers the incoming call from the carrier network **216** and retrieves an appropriate announcement (e.g., a welcome greeting) from a database, server or browser. The communication node **212** then plays the announcement to the caller. In response to audio inputs from the end user, the communication node **212** retrieves information from a destination or database of one or more of the information sources, such as the content providers **208**, **221** or the markup language servers **209**, **251**, **253**, **257**. After the communication node **212** receives the information, it provides a response to the end user based upon the retrieved information.

The communication node **212** can provide various dialog voice personalities (e.g., a female voice, a male voice, etc.), and can implement various grammars (e.g., vocabulary) to detect and respond to the audio inputs from the end user. In addition, the communication node **212** can automatically select various speech recognition models (e.g., English, Spanish or English accent models) based upon an end user's profile, communication device and/or speech patterns. The communication node **212** can also allow the end user to select a particular speech recognition model.

When an end user accesses the electronic network **206** from a communication device **201**, **202**, **203**, **204**, **205** registered with the system (e.g., home telephone, work telephone, cellular telephone, etc.), the communication node **212** can by-pass an end user screening option and automatically identify the end user (or the type of communication device) through the use of ANI or CLI. After the communication node **212** verifies the call, the communication node **212** provides a greeting (e.g., "Hi, this is your personal agent, Maya. Welcome Bob. How may I help you?"). The communication node **212** then enters into a dialogue with the end user, and the end user can select a variety of services offered by the communication node **212**.

When the end user accesses the electronic network **206** from a communication device not registered with the system (e.g., a payphone, a telephone of a non-end user, etc.), the communication node **212** answers the call and prompts the end user to enter his or her name and/or a personal identification number (PIN) using voice commands or DTMF signals. The communication node **212** can also utilize speaker verification to identify the particular speech pattern of the end user. If the communication node **212** authorizes the end user to access the system, the communication node **212** provides a personal greeting to the end user (e.g., "Hi, this is your personal agent, Maya. Welcome Ann. How may I help you?").

The communication node **212** then enters into a dialogue with the end user, and the end user can select various services offered by the communication node **212**. If the name and/or PIN of the end user cannot be recognized or verified by the communication node **212**, the end user will be routed to a customer service representative.

Once the end user has accessed the communication system **200**, the end user may implement a wide variety of services and features by using voice commands, such as, for example, voice dialing, voice paging, facsimiles, caller announcements, voice mails, reminders, call forwarding, call recording, content information (e.g., newspapers, etc.), read email, read calendars, read "to-do" lists, banking, e-commerce. The communication system **200** can place outbound calls and pages to business and personal parties or contacts (e.g., friends, clients, business associates, family members, etc.) in response to DTMF signals or voice commands. The calls can be routed through a telephone or electronic network to the selected party and the pagers can be sent to a selected party via a paging system. The communication system **200** can also receive calls routed through a telephone or electronic network.

As shown in **FIG. 5**, the communication node **212** preferably includes a telephone switch **230**, a voice or audio recognition (VRU) client **232**, a VRU server **234**, a controller or call control unit **236**, an Operation and

Maintenance Office or a billing server unit **238**, a LAN **240**, an application server unit **242**, a database server unit **244**, a gateway server or router firewall server unit **246**, a VOIP unit **248**, a voice browser **250**, a voice markup language server **251**, a messaging server **255** and a data markup language server **253**. Although the communication node **212** is shown as being constructed with various types of independent and separate units or devices, the communication node **212** can be implemented by one or more integrated circuits, microprocessors, microcontrollers or computers which may be programmed to execute the operations or functions equivalent to those performed by the devices or units shown. It will also be recognized that the communication node **212** can be carried out in the form of hardware components and circuit designs and/or software or computer programs.

The communication node **212** can be located in various geographic locations throughout the world or the United States (e.g., Chicago, IL). The communication node **212** can be operated by one or more carriers (e.g., Sprint, Qwest, MCI, etc.) or independent service providers (e.g., Motorola, Inc.).

The communication node **212** can be integrated with the carrier network **216** or can be located remote from the carrier network **216**. It is also contemplated that the communication node **212** may be integrated into a communication device, such as, for example, a wire-line or wireless telephone, a radio device, a PC, a PDA, a PIM, etc., and can be programmed to connect or link directly to an information source.

The communication node **212** can also be configured as a standalone system to allow end users to dial directly into the communication node **212** via a direct access telephone number. In addition, the communication node **212** may comprise a telephony switch (e.g., a PBX or Centrix unit), an enterprise network or a LAN. In this configuration, the communication system **200** can be implemented to automatically connect an end user to the communication node **212** when the end user accesses a communication device.

When the telephone switch **230** receives an incoming call from the carrier network **216**, the call control unit **236** sets up a connection in the telephone switch **230** to the VRU client **232**. The communication node **212** then enters into a dialog with the end user regarding various services and
5 functions. The VRU client **232** preferably generates pre-recorded voice announcements and/or messages to prompt the end user to provide inputs to the communication node **212** using voice commands or DTMF signals.

In response to the inputs from the end user, the communication node **212** retrieves information from a destination of one of the information sources
10 and provides outputs to the end user.

The telephone switch **230** is preferably connected to the VRU client **232**, the VOIP unit **248** and the LAN **240**. The telephone switch **230** receives incoming calls from the carrier network **216**. The telephone switch **230** also receives incoming calls from the communication device **202** routed over the
15 Internet **220** via the VOIP unit **248**. The telephone switch **230** also receives messages and pages from communication devices **203**, **205**, respectively. The telephone switch **230** is preferably a digital cross-connect switch, Model LNX, available from Excel Switching Corporation, Hyannis, MA. It will be recognized that the telephone switch **230** can be any suitable switch.

The VRU client **232** is preferably connected to the VRU server **234** and the LAN **240**. The VRU client **232** processes voice communications, DTMF signals, pages and messages (e.g., emails). Upon receiving voice communications, the VRU client **232** routes the speech communications to the VRU server **234**. When the VRU client **232** detects DTMF signals, it
20 sends a command to the call control unit **236**. It will be recognized that the VRU client **232** can be integrated with the VRU server **234**.

The VRU client **232** preferably comprises a PC, such as, for example, a Windows NT compatible PC, with hardware capable of connecting individual telephone lines directly to the telephone switch **230** or carrier
30 network **216**. The VRU client **232** preferably includes a microprocessor, random access memory, read-only memory, a T1 or ISDN interface board,

and one or more voice communication processing boards (not shown). The voice communication processing boards are preferably Dialogic boards, Antares Model, available from Dialogic Corporation, Parsippany, NJ. The voice communication boards may include a voice recognition engine having a vocabulary for detecting a speech pattern. The voice recognition engine is preferably a RecServer software package, available from Nuance Communications, Menlo Park, CA.

The VRU client **232** can also include an echo canceler (not shown) to reduce or cancel TTS or playback echoes transmitted from the PSTN **214** due to hybrid impedance mismatches. The echo canceler is preferably included in an Antares Board Support Package, also available from Dialogic.

The call control unit **236** is preferably connected to the LAN **240**, and sets up the telephone switch **230** to connect incoming calls to the VRU client **232**. The call control unit **236** also sets up incoming calls or pages to the communication node **212** over the Internet **220** and pages and messages sent from the communication devices **203**, **205** via the paging network **211** and email system **213**, respectively. The control call unit **236** preferably comprises a PC, such as, for example, a Windows NT compatible PC.

The LAN **240** allows the various components and devices of the communication node **212** to communicate with each other via twisted pair, fiber optic, coaxial cables or the like. The LAN **240** may use Ethernet, Token Ring or other suitable types of protocols. The LAN **240** is preferably a 100 Megabit per second Ethernet switch, available from Cisco Systems, San Jose, CA, and can comprise any suitable network system. The communication node **212** may include a plurality of LANs.

The VRU server **234** is connected to the VRU client **232** and the LAN **240**. The VRU server **234** receives voice communications from the end user via the VRU client **232**. The VRU server **234** processes the voice communications and compares the voice communications against a vocabulary or grammar stored in the database server unit **244** or a similar memory device.

5 The VRU server **234** provides output signals, representing the result of the voice communications processing, to the LAN **240**. The LAN **240** routes the output signal to the call control unit **236**, the application server unit **242** and/or the voice browser **250**. The communication node **212** then performs a specific function associated with the output signals.

10 The VRU server **234** preferably includes a TTS unit **252**, an automatic speech recognition (ASR) unit **254**, and a STT unit **256**. The TTS unit **252** receives textual data or information (e.g., email, web pages, documents, files, etc.) from the application server unit **242**, the database server unit **244**, the call control unit **236**, the gateway server unit **246**, the application server unit **242** and the voice browser **250**. The TTS unit **252** processes the textual data and converts the data to voice data or information.

15 The TTS unit **252** can provide data to the VRU client **232**, which reads or plays the data to the end user. For example, when the end user requests information (e.g., news updates, stock information, traffic conditions, etc.), the communication node **212** retrieves the desired data (e.g., textual information) from a destination of the one or more of the information sources and converts the data via the TTS unit **252** into a response.

20 The response is then sent to the VRU client **232**. The VRU client **232** processes the response and reads an audio message to the end user based upon the response. It is contemplated that the VRU server **234** can read the audio message to the end user using human recorded speech or synthesized speech. The TTS unit **252** is preferably a TTS 2000 software package, available from Lernout and Hauspie Speech Product NV, Burlington, MA.

25 The ASR unit **254** provides speaker dependent or independent automatic voice recognition of voice communications from the end user. It is contemplated that the ASR unit **254** can include speaker dependent voice recognition. The ASR unit **254** processes the voice communications to determine whether a word or a speech pattern matches any of the grammars or vocabulary stored in the database server unit **244** or downloaded from the
30 voice browser **250**. When the ASR unit **254** identifies a selected speech

pattern of the voice communications, the ASR unit **254** sends an output signal to implement the specific function associated with the recognized speech pattern. The ASR unit **254** is preferably a speaker independent voice recognition software package, RecServer Model, also available from Nuance Communications. It is contemplated that the ASR unit **254** can be any suitable voice recognition unit to detect voice communications.

The STT unit **256** receives voice communications and converts the voice communications to textual information (e.g., a text message). The textual information can be sent or routed to the communication devices **201**, **202**, **203**, **204**, **205**, the content providers **208**, **221**, the markup language servers **209**, **251**, **253**, **257**, the voice browser **250** and the application server unit **242**. The STT unit **256** is preferably a Naturally Speaking software package, available from Dragon Systems, Newton, MA.

The VOIP unit **248** is preferably connected to the telephone switch **230** and the LAN **240**. The VOIP unit **248** allows an end user to access the communication node **212** via the Internet **220** or VOIP public network using voice commands. The VOIP unit **248** can receive VOIP protocols (e.g., H.323 protocols) transmitted over the Internet **220** or Intranet, and can convert the VOIP protocols to voice information or data. The voice information can then be read to the end user via the VRU client **232**.

The VOIP unit **248** can also receive voice communications from the end user and convert the voice communications to a VOIP protocol that can be transmitted over the Internet **220**. The VOIP unit **248** is preferably a Voice Net software package, also available from Dialogic Corporation. It will be recognized that the VOIP unit **248** can be incorporated into a communication device.

The communication node **212** also includes a detection unit **260**. The detection unit **260** is preferably a phrase or key word spotter unit, detecting incoming audio inputs or communications or DTMF signals from the end user. The detection unit **260** is preferably incorporated into the telephone switch **230**, but can be incorporated into the VRU client **232**, the carrier network **216**

or the VRU server **234**. The detection unit **260** is preferably included in a RecServer software package, also available from Nuance Communications.

The detection unit **260** records the audio inputs from the end user and compares the audio inputs to the vocabulary or grammar stored in the database server unit **244**. The detection unit **260** continuously monitors the end user's audio inputs for a key phrase or word after the end user is connected to the node **212**. When the detection unit **260** detects the key phrase or word, the VRU client **232** plays a pre-recorded message to the end user. The VRU client **232** then responds to the audio inputs provided by the end user.

The billing server unit **238** is preferably connected to the LAN **240**. The billing server unit **238** can record data about the use of the communication node **212** by an end user (e.g., length of calls, features accessed by the end user, etc.). Upon completion of a call by an end user, the call control unit **236** sends data to the billing server unit **238**. The billing server unit **238** can subsequently process the data in order to prepare customer bills. The billing server unit **238** can use the ANI or CLI of the communication device to properly bill the end user. The billing server unit **238** preferably comprises a Windows NT compatible PC.

The gateway server unit **246** is preferably connected to the LAN **240** and the Internet **220**. The gateway server unit **246** provides access to the content provider **221** and the voice markup language server **257** via the Internet **220**. The gateway server unit **246** allows end users to access the communication node **212** from the communication device **202** via the Internet **220**. The gateway server unit **246** can function as a firewall to control access to the communication node **212** to authorized end users. The gateway server unit **246** is preferably a Cisco Router, also available from Cisco Systems.

The database server unit **244** is preferably connected to the LAN **240**. The database server unit **244** preferably includes a plurality of storage areas to store data relating to end users, such as, for example, speech vocabularies, dialogs, personalities, end user entered data, and other

information. Preferably, the database server unit **244** stores a personal file or address book. The personal address book can contain information required for the operation of the communication system **200**, including end user reference numbers, personal access codes, personal account information,
5 contact's addresses, telephone numbers, etc. The database server unit **244** is preferably a PC, such as, for example, a Windows NT compatible PC.

The application server unit **242** is preferably connected to the LAN **240** and the content provider **208**. The application server unit **242** allows the communication node **212** to access information from a destination of the
10 information sources, such as the content providers **208**, **221** and the markup language servers **209**, **251**, **253**, **257**. For example, the application server unit **242** can retrieve information (e.g., weather reports, stock information, traffic reports, restaurants, flower shops, banks, calendars, "to-do" lists, e-commerce, etc.) from a destination of the information sources. This
15 application server unit **242** may include Starfish Software to provide the address book, calendar and to-do lists, and to allow the end user to organize information. The application server unit **242** processes the retrieved information and provides the information to the VRU server **234** and the voice browser **250**. The VRU server **234** can provide an audio announcement to
20 the end user based upon the information using TTS synthesizing or human recorded voice. The application server unit **242** can also send tasks or requests (e.g., transactional information) received from the end user to the information sources (e.g., a request to place an order for a pizza). The application server unit **242** can further receive end user inputs from the VRU
25 server **234** based upon a speech recognition output. The application server unit **242** is preferably a PC.

The voice markup language server **251** is preferably connected to the LAN **240**. The voice markup language server **251** can include a database, scripts and markup language documents or pages. The voice markup
30 language server **251** is preferably a PC, such as, for example, a Windows NT

compatible PC. It will also be recognized that the voice markup language server **251** can be an Internet server (e.g., a Sun Microsystems server).

The messaging server **255** is preferably connected to the LAN **240**, the paging network **211**, an email system **213** and a short message system (SMS) **290**. The messaging server **255** routes pages between the LAN **240** and the paging network **211**. The messaging server **255** is preferably a PC, such as, for example, a Windows NT compatible PC. The messaging server **255** can also provide direct storage. It is contemplated that the messaging server **255** can reside externally from the communication node **212**.

The voice browser **250** is preferably connected to the LAN **240**. The voice browser **250** preferably receives information from the markup language servers **209**, **251**, **253**, **257**, the database server unit **244** and the content providers **208**, **221**. In response to voice commands or DTMF signals, the voice browser **250** generates a content request (e.g., an electronic address) to navigate to a destination of one or more of the information sources. The content request can use at least a portion of a Uniform Resource Locator, an Internet Protocol, a page request, or email.

After the voice browser **250** is connected to an information source, the voice browser **250** preferably uses a Transmission Control Protocol/Internet Protocol connection to pass requests to the information source. The information source responds to the requests, sending at least a portion of the requested information, represented in electronic form, to the voice browser **250**. The information can be stored in a database, and can include text content, markup language document or pages, non-text content, dialogs, audio sample data, recognition grammars, etc. The voice browser **250** then parses and interprets the information, further described below. The voice browser **250** can be integrated into the communication devices **201**, **202**, **203**, **204**, **205**.

As shown in **FIG. 5**, the content provider **208** is connected to the application server unit **242** of the communication node **212**, and the content provider **221** is connected to the gateway server unit **246** of the

10 The voice mail unit **274** is preferably connected to the telephone switch
203 and the LAN **240**. The voice mail unit **274** can store voice mail
messages from parties trying to send messages to the communication node
212. When an end user accesses the electronic network **206**, the voice mail
unit **274** can notify the end user of new and stored messages. The end user
15 can access the messages to play, delete, store and forward the messages.
When the end user accesses a message, the message can be read to the
end user or can be displayed as textual information on a communication
device (e.g., a pager, a SMS **290**, or a PDA, etc.). The end user can also
access and operate external messages or mail systems remote from the
20 electronic network **206**.

The FAX server unit **272** is preferably connected to the telephone switch **230** and the LAN **240**. The FAX server unit **272** receives and stores facsimile information sent via the electronic network **206** or the carrier network **216**. Subscribers can access the facsimile information to play, store, delete, and forward the information. The facsimile information can be read via the TTS unit **252** or can be displayed as textual information on a suitable communication device. The FAX server unit **272** preferably comprises a PC, such as, for example, a Windows NT compatible PC or a Dialogue Fax Server.

30 Further information regarding communication system **200** is disclosed
in U.S. Patent Application No. 09/141,485, entitled Telecommunication

System and Methods Therefor, filed August 27, 1998, the entire disclosure of which is incorporated herein.

It should be appreciated that the embodiments described above are to be considered in all respects only illustrative and not restrictive. The scope of the invention is indicated by the following claims rather than by the foregoing description. All changes that come within the meaning and range of equivalents are to be embraced within their scope.

WE CLAIM:

1. A method of assisting an end user comprising the steps of:
5 device;
determining an assistance center in close proximity to the
communication device to provide assistance to the end user;
forwarding a second assistance request signal to the assistance
center;
10 receiving a first response signal from assistance center; and
transmitting a second response signal to the communication
device.
2. The method of claim 1, wherein the determining step locates an
15 assistance center closest to the end user.
3. The method of claim 1, wherein the communication device
switches to a passive mode after transmitting the assistance request signal.
- 20 4. The method of claim 1, wherein the assistance request signal
includes a geographic location of the communication device.
5. The method of claim 4, wherein the geographic location
comprising at least one geographic coordinate.
25
6. The method of claim 5, wherein the geographic coordinates
include one of a Global Positioning System coordinate and cell and sector
coordinate.

7. The method of claim 1, wherein the communication device includes one of a telephone, a paging unit, a cellular telephone, a satellite telephone and an Internet telephone.

5 8. A system for assisting an end user comprising:
computer readable program code to process a first assistance
request signal from a communication device;
computer readable program code to select an assistance center
based upon the first assistance request signal;
10 computer readable program code to forward a second
assistance request signal to an assistance center;
computer readable program code to receive a first response
signal from the assistance center; and
computer readable program code to transmit a second response
15 signal to the communication device.

9. A program for assisting an end user comprising:
computer readable program code to receive a first assistance
request signal from a communication device;
20 computer readable program code to forward a second
assistance request signal to an assistance center;
computer readable program code to receive a first response
signal from the assistance center; and
computer readable program code to transmit a second response
25 signal to the communication device.

30

10. A method of determining the location of an end user comprising the steps of:

receiving a first signal from a first communication device at a communication node;

5 transmitting a second signal from the communication node to a second communication device;

receiving a first response signal from the second communication device at the communication node, the first response signal including a geographic location of the communication device; and

10 transmitting the geographic location to the first communication device from the communication node in response to the first response signal.

11. The method of claim 10, further including the step of transmitting an identification signal from the first communication device to the communication node when the first signal is received.

12. The method of claim 10, wherein the first response signal includes an authorization signal and a unique identifying signal.

20 13. The method of claim 10, wherein the first response signal includes an instruction to transmit the second response signal to the first communication device.

25 14. The method of claim 10, wherein the geographic location includes a set of coordinates of the second communication device.

15. The method of claim 12, wherein the geographic location includes at least one of a global positioning system coordinate and an infrastructure-based coordinate.

30

16. The method of claim 15, further comprising the steps of:
comparing the unique identifying signal to a stored unique
identifying signal corresponding to the subscriber;
determining an assistance center near the second
5 communication device if the unique identifying signal does not match the
stored unique identifying signal; and
providing assistance to the end user if the unique identifying
signal does not match the stored unique identifying signal.

10 17. The method of claim 10, wherein the first communication device
includes one of a telephone, a paging unit, a cellular telephone, a satellite
telephone and an Internet telephone.

15 18. The method of claim 10, wherein the second communication
device includes one of a telephone, a paging unit, a cellular telephone, a
satellite telephone and an Internet telephone.


20 19. A system for assisting an end user comprising:
a communication node in communication with a first
communication device and a second communication device;
computer readable program code to receive an instruction signal
from the first communication device at the communication node;
computer readable program code to transmit an information
signal from the communication node to the second communication device;
25 computer readable program code to receive a first response
signal from the second communication device at the communication node;
and
computer readable program code to transmit a second response
signal to the first communication device from the communication node when
30 instructed to do so by the first response signal.

20. A program for assisting an end user comprising:
computer readable program code to receive an instruction signal
from the first communication device at a communication node;
computer readable program code to transmit an information
5 signal from the communication node to the second communication device;
computer readable program code to receive a first response
signal from the second communication device at the communication node;
and
computer readable program code to transmit a second response
10 signal to the first communication device from the communication node when
instructed to do so by the first response signal.

21. A communication system for assisting an end user comprising:
a communication node to receive a request from a first
15 communication device, the request including a geographic location of the first
communication device; wherein
the communication node determines an assistance center to
provide assistance to the end user in response to the request and transmits a
service request to the assistance center; and the communication node
20 transmits information to the end user in response to a response signal from
the assistance center.

ABSTRACT OF THE DISCLOSURE

A method of assisting an end user is provided. A first assistance request signal is received from a communication device. A communication node determines an assistance center in close proximity to the communication device to provide assistance to the end user. The communication node then forwards a second assistance request signal to the assistance center. The communication node receives a first response signal from the assistance center. Finally, the communication node transmits a second response signal to the communication device.

FIG. 1





FIG. 2

FIG. 4



Prior U.S. Applications(s):

(check
one) X no such applications filed. such applications identified as follows:

(Application Serial No.)	(Filing Date)	(Status) (Patented, Pending, Abandoned)
(Application Serial No.)	(Filing Date)	(Status) (Patented, Pending, Abandoned)
(Application Serial No.)	(Filing Date)	(Status) (Patented, Pending, Abandoned)

I hereby declare that: as to any claimed subject matter of this application which is common to my earlier United States or foreign application(s), if any, which I have identified above and claimed the benefit of priority thereof, I do not believe that the same was ever known or used in the United States before my invention thereof or patented or described in any printed publication in any country before my invention thereof or more than one year prior to the first of said earlier application(s), or in public use or on sale in the United States more than one year prior to the first of said earlier application(s), and that the said common subject matter has not been patented or made the subject of an inventor's certificate before the date of the first of said earlier U.S. application(s) in any country foreign to the United States on an application, filed by me or my legal representatives or assigns more than twelve months (six months if the present application is a Design patent application) prior to the first of said earlier U.S. application(s), if any; and that, as to any claimed subject matter of this application which is not common to said earlier application(s), if any, I do not know and do not believe that the same was ever known or used in the United States before my invention thereof or patented or described in any printed publication in any country before my invention thereof or more than one year prior to the date of this application, or in public use or on sale in the United States more than one year prior to the date of this application, and that said subject matter has not been patented or made the subject of an inventor's certificate in any country foreign to the United States on an application filed by me or my legal representatives or assigns more than twelve months (six months if the present application is a Design patent application) prior to the date of this application.

I HEREBY APPOINT THE FOLLOWING AS MY ATTORNEY(S) OR AGENT(S) WITH FULL
POWER
OF SUBSTITUTION TO PROSECUTE THIS APPLICATION AND TRANSACT ALL BUSINESS IN
THE PATENT AND TRADEMARK OFFICE CONNECTED THEREWITH:

NAME(S)	REGISTRATION NO.(S)	ASSOCIATE POWER OF ATTORNEY ATTACHED
Steven G. Parmelee	28,790	
Jonathan P. Meyer	30,477	
James E. Gauger	38,154	
Douglas D. Fekete	29,065	
Daniel K. Nichols	29,420	
J. Ray Wood	36,062	

<u> </u>	<u> X </u>
Yes	No

Send Written Correspondence To:

James E. Gauger

MOTOROLA, INC.
1303 East Algonquin Road
Schaumburg, IL 60196

Direct Telephone Calls to: (708) 576-0053

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statement and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor			NANDAKISHORE A. ALBAL		
Inventor's signature			<i>Nandakishore A. Albal</i>		
Date			APRIL 6, 2000		
Residence		Naperville	IL		
		City	State or Foreign Country		
Citizenship		USA			
Post Office Address		2731 Gleneagles Court			
		Street Address			
		Naperville	IL	60565	
		City	State or Country	Zip Code	

Full name of sole or first inventor			WALTER COOK, JR.		
Inventor's signature					
Date					
Residence		Chicago	IL		
		City	State or Foreign Country		
Citizenship		USA			
Post Office Address		2140 N. Magnolia Avenue			
		Street Address			
		Chicago	IL	60614	
		City	State or Country	Zip Code	

Direct Telephone Calls to: (708) 576-0053

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statement and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor NANDAKISHORE A. ALBAL

Inventor's signature _____

Date _____

Residence Naperville IL
City State or Foreign Country

Citizenship USA

Post Office Address 2731 Gleneagles Court
Street Address

Naperville IL 60565
City State or Country Zip Code

Full name of sole or first inventor WALTER COOK, JR.

Inventor's signature Walter Blackwell Cook, Jr.

Date 4/7/00

Residence Chicago IL
City State or Foreign Country

Citizenship USA

Post Office Address 2140 N. Magnolia Avenue
Street Address

Chicago IL 60614
City State or Country Zip Code